


# Two-Level Fronthaul Architecture and Requirements

Liuyan Han and Jinri Huang  
China Mobile



# Compliance with IEEE Standards Policies and Procedures

**Subclause 5.2.1 of the *IEEE-SA Standards Board Bylaws* states, "While participating in IEEE standards development activities, all participants...shall act in accordance with all applicable laws (nation-based and international), the IEEE Code of Ethics, and with IEEE Standards policies and procedures."**

The contributor acknowledges and accepts that this contribution is subject to

- The IEEE Standards copyright policy as stated in the *IEEE-SA Standards Board Bylaws*, section 7, <http://standards.ieee.org/develop/policies/bylaws/sect6-7.html#7>, and the *IEEE-SA Standards Board Operations Manual*, section 6.1, <http://standards.ieee.org/develop/policies/opman/sect6.html>
- The IEEE Standards patent policy as stated in the *IEEE-SA Standards Board Bylaws*, section 6, <http://standards.ieee.org/guides/bylaws/sect6-7.html#6>, and the *IEEE-SA Standards Board Operations Manual*, section 6.3, <http://standards.ieee.org/develop/policies/opman/sect6.html>

**IEEE 1914.1 TF  
1914 NGFI WG  
Jinri Huang, huangjinri@chinamobile.com**

**Two-Level Fronthual Architecture and Requirements**

**Date:** 2017-01-10


**Author(s):**

<b>Name</b>	<b>Affiliation</b>	<b>Phone [optional]</b>	<b>Email [optional]</b>
Liuyan Han	China Mobile		hanliuyan@chinamobile.com
Jinri Huang	China Mobile		huangjinri@chinamobile.com

# Outline

- Two-level fronthaul architecture
- Discussions on delay requirement
- Discussions on synchronization requirement


# Two-level fronthaul architecture




- 5G C-RAN BBU will be divided into the functional entities of CU and DU.
- Accordingly, the fronthaul domain will include two levels:
  - Domain I between RRU and DU
  - Domain II between DU and CU
- It is proposed to study and define the requirements for the fronthaul domain I and domain II, respectively.

# Two-level fronthaul architecture

- A typical 5G metro network architecture
- Including the backhaul and fronthaul transport networks, which may be emerged by utilizing the same fiber resources and transport equipments.



# Functional splits and requirements for fronthaul I and II




- Fronthaul Domain I
  - High bandwidth, stringent delay and synchronization
  - Possible to use lower layer function split
- Fronthaul Domain II
  - Lower bandwidth, less stringent delay and synchronization
  - Possible to use higher layer function split

*Clarification: the architecture here is in line with Jouni's architecture proposal;*

# A typical fronthaul aggregation scenario

- Basic assumption:
  - eCPRI b/w RRU and FTN I
  - 100MHz, DL 256QAM, 16 layers
  - Option 2 split b/w CU and DU
  - 1 DU ~ 6 fronthaul transport node I (FTN I)
  - 1 CU ~ 6 DU ~ 6 FTN II




$$\begin{aligned} & (\text{eCPRI rate}) * (\# \text{ of optical module per RRU}) * \\ & (\# \text{ of FTN I}) * (\# \text{ of RRU per FTN I}) * \\ & = 25 * 2 * 6 * 3 = 900 \text{ Gbps} \end{aligned}$$

Note: multiplexing gain not considered yet;



# A typical fronthaul aggregation scenario


- Basic assumption:
  - eCPRI b/w RRU and FTN I
  - 100MHz, DL 256QAM, 16 layers
  - Option 2 split b/w CU and DU
  - 1 DU ~ 6 fronthaul transport node I (FTN I)
  - 1 CU ~ 6 DU ~ 6 FTN II



- Basic rate: Option 2 FH rate: 4Gbps according to 3GPP
- Given 1DU ~ 18 RRU, the data rate here is:  
= 4Gbps \* 18 = 72 Gbps
- Note: multiplexing gain not considered yet;

# A typical fronthaul aggregation scenario

- Basic assumption:
  - eCPRI b/w RRU and FTN I
  - 100MHz, DL 256QAM, 16 layers
  - Option 2 split b/w CU and DU
  - 1 DU ~ 6 fronthaul transport node I (FTN I)
  - 1 CU ~ 6 DU ~ 6 FTN II




$72 \text{ Gbps} * 6 \text{ DU per CU}$   
 $= 432 \text{ Gbps}$

Note: multiplexing gain not considered yet;

# Outline

- Two-level fronthaul architecture
- Discussions on delay requirement
- Discussions on synchronization requirement

# Discussions on delay requirement




- The fronthaul delay requirement depends on several factors:
  - 5G user plane latency requirement, which is 4ms for eMBB and 0.5ms for URLLC.
  - HARQ Loop period requirement, which has not been defined for 5G.
  - Function split options
- Assumption: Low-MAC resides in DU part
  - Fronthaul domain I latency: mainly impacted by HARQ
  - Fronthaul domain II latency: mainly consider DP latency impact
- *Clarification: not contradictory with other proposals, mainly from NW perspective*

# Outline

- Two-level fronthaul architecture
- Discussions on delay requirement
- Discussions on synchronization requirement


# 5G synchronization requirement



5G synchronization requirement comes from:

- Carrier aggregation (CA): the inter-band CA would probably be used for the inter-site scenario, which requires 260ns TAE between RRUs.
- Joint Transmission (JT): which requires 260ns TAE between RRUs.
- 5G frame structure: which is under study. In 5G, the frame structure will probably be changed with shorter cyclic prefix (CP) length, which will require more stringent air-interface synchronization compared with 1.5us for TD-LTE.
- Positioning service by the mobile communication: 5G shall support higher accuracy location capability that is less than [3 m], which needs 10ns synchronization accuracy.

# Fronthaul synchronization requirement



- The fronthaul synchronization should satisfy the end-to-end network budget, while it is better to satisfy the positioning service requirement in the CRAN architecture.
- According to the time error allocation on the whole time distribution chain, it is proposed that:
  - The fronthaul domain I:  $\pm 10\text{ns}$  (to support positioning service)
  - The fronthaul domain II:  $\pm 20\text{ns}$  (related to the synchronization hops)

# Thank you!